

HUNTER 26 RIGGING SPECIFICATIONS

STANDING RIGGING

Item	Quantity	Wire Diameter	Mast Fitting	Deck Fitting	Length	Measurement Points
Forestay	1	3/16" 1x19 SS	Stem Ball	Turnbuckle w/ Toggle	30'-7 5/8"	Inside of Stem Ball to Center of Pin
Upper Shroud	2	3/16" 1x19 SS	T-Ball	Turnbuckle w/ Toggle	29'-11"	Inside of T Ball to Center of Pin
Lower Shroud	2	3/16" 1x19 SS	T-Ball	Turnbuckle w/ Toggle	16'-0"	Inside of Stem Ball to Center of Pin
Mast Raising Bridle Wires	2	1/8" 1x19 SS	T-Ball	Pelican Hook	5'-11"	Inside of T-Ball to Center of Pelican Hook

RUNNING RIGGING

Item	Quantity	Line Spec	Length	Fittings
Main Halyard	1	5/16 Yacht Braid	81'	Shackle
Jib Halyard	1	5/16 Yacht Braid	72'	Shackle
Spin Halyard	1	5/16 Yacht Braid	73'	Shackle (Optional)
Main Sheet	1	3/8 Yacht Braid	70'	Eye Splice
Jib Sheets	1	3/8 Yacht Braid	50'	B.B.E.
Spinnaker Sheets	2	3/8 Yacht Braid	40'	Snap Shackles (Optional)
Topp. Lift	1	1/4 Yacht Braid	35'	B.B.E.*
Spin. Pole up/down	1	5/16 Yacht Braid	38'	Snap Shackles (Optional)
Vang	1	1/4 Yacht Braid	20'	Eye Splice
Outhaul	1	5/16 Yacht Braid	16'	B.B.E.
Reef	1	5/16 Yacht Braid	32'	B.B.E.
Rudder Uphaul	1	3/8 Yacht Braid	10'	B.B.E. (Hunter)#RI0312
C/B Uphaul	1	7/16 Yacht Braid	11'	B.B.E. (Hunter)#RI0312
C/B Cascade	1	5/16 Yacht Braid	12'	B.B.E.
Anchor Rode	1	3/8 Nylon	100'	Shackle & Thimble
Furling Pennant	1	3/16 Yacht Braid	40'	B.B.E. (Optional)

*B.B.E. - Burned Both Ends