

VISION 32 RIGGING SPECIFICATIONS

STANDING RIGGING

FITTINGS

<u>Description</u>	<u>Wire Size</u>	<u>Upper End</u>	<u>Lower End*</u>	<u>Overall Length</u>
Headstay	7/32 1x19	Marine eye	7-12-12	33'9 3/4"

* "X-X-X" represents the turnbuckle size as follows:
Wire size - body size - pin diameter in 32nd's of an inch. Example "
7-12-12 is a diameter in the turnbuckle that accepts a 7/32" wire, has a
3/8", (12/32"), thread diameter in the body, and uses a 3/8", (12/32") pin..

RUNNING RIGGING

<u>Line</u>	<u>Size</u>	<u>Attachments</u>	<u>Overall Length</u>
Main Halyard	7/16"	Headboard shackle	115'
Jib Halyard	3/8"	Snapshackle	83'
Main Sheet	7/16"	Eye splice	56'
Jib Sheet	3/8"		35'
Traveller Control Lines	3/8"	Eye splice	19'
Lazy Jack	3/8"		50'
Lazy Jack Vinyl	3/16" 7x7	Two Thimbles	20'
Anchor Line	1/2"	Shackle	150'

All lines low stretch Dacron except anchor line which is nylon.

All rigging is supplied by SECO SOUTH.