

## 356 SOP V-BERTH PLASTIC HEADLINER PANELS INSTALLATION



#	Qty.	Description	Size	Part #	
1	1	Plastic V-Berth Port Panel	356	259035	
2	1	Plastic V-Berth Center Panel	356		
3	1	Plastic V-Berth Starboard Panel	356	259033	
4	9	Port Panel Fasteners	Beige	# 8 x 3/4" T H	467985
5	6	Center Panel Fasteners	Beige	# 8 x 3/4" T H	467985
6	9	Starboard Panel Fasteners	Beige	# 8 x 3/4" T H	467985

There are three plastic headliner panels in the V-Berth, one port, one center and one starboard.

1. Place the port panel on the port side of the V-Berth, making sure the aft end is flush with the aft bulkhead.
2. Secure the panel using designated fasteners in the designated grommets. The grommets are pre-installed by the plastic shop.
3. Place and secure the starboard side described as above with the port side.
4. Place and center the center panel over the port and starboard panels on the fwd end of the V-Berth headliner. Making sure that the recesses fit over the panels.
5. Secure using the designated fasteners, the first two fasteners will be 3" aft of the fwd end of panel, 1/2" inboard of each side of the panel and 2" between the two fasteners. The next two will be 10-1/2" aft from the first two fasteners, 1/2" inboard of each side of the panel and 2" between the two fasteners. The last two fasteners will be 3/4" fwd from the aft end of the panel, 1/2" inboard of each side of the panel and 2" between the two fasteners.

Revision Dates:

Expected Time: 60 min.

Page

# 356 SOP MAIN CABIN PLASTIC HEADLINER PANELS INSTALLATION



#	Qty.	Description	Size	Part #
1	1	Plastic Main Cabin Port Fwd Panel	356	
2	1	Plastic Main Cabin Port Aft Panel	356	
3	1	Plastic Main Cabin Starboard Fwd Panel	356	
4	1	Plastic Main Cabin Starboard Aft Panel	356	
5		Port Panel Fasteners      Beige	# 8 x 3/4" T H	467985
6		Starboard Panel Fasteners      Beige	# 8 x 3/4" T H	467985

There are four plastic headliner panels in the Main Cabin, one port fwd, one port aft, one starboard fwd, and one starboard aft.

1. Place the port fwd panel on the port side of the Main Cabin, making sure the fwd end is flush with the fwd bulkhead.
2. Pull the light wires through the appropriate holes.
3. Secure the panel using designated fasteners in the designated grommets. The grommets are pre-installed by the plastic shop.
4. Place and secure the starboard fwd side described as above like the port fwd side.
5. Place two pieces of 1/4" x 1/12" x 3" (sizes may vary) Meranti wood under the mid section of the fwd and aft panels to help hold the panels up for installation. These are temporary.
6. Installation for the port and starboard aft panels may require two people, one to hold the panel in place and one to secure the panel in place.
7. Place the port aft panel over the chart locker flush with the aft Main Cabin bulkhead. Pull the light wires through.
8. After the port and starboard aft panels are installed cut around the chainplates bolts using a dremel router bit.
9. Place the starboard aft panel over the galley flush with the aft Galley bulkhead. Pull the light wires through.
10. Secure using the designated fasteners.
11. Prop up the two pieces up with the 1/4" Meranti wood.

Revision Dates:

Expected Time: 90 min.

Page

# 356 SOP MAIN CABIN PLASTIC CHAINPLATE PANELS INSTALLATION



#	Qty.	Description	Size	Part #
1	1	Plastic Main Cabin Port Chainplate Panel	356	
2	1	Plastic Main Cabin Starboard Chainplate Panel	356	
3	8	Port Chainplate Panel Fasteners      Beige	# 8 x 3/4" T H	467985
4	8	Starboard Chainplate Panel Fasteners      Beige	# 8 x 3/4" T H	467985

1. The two chainplate covers will be installed after the Whisper has been completely installed.
2. The chain plate covers are located in the mid port and starboard sides of the headliner.
3. To install the port chainplate cover, place the cover centered over the two port plastic headliner panels, fitting the curves in the correct places for a snug fit.
4. Secure using the designated fasteners. The first two fasteners will be 1-1/4" inboard of the bottom end of panel, 1/2" inboard of each side of the panel and 2" between the two fasteners. The top two will be 3" down from the top of the panel, 1/2" inboard of each side of the panel and 2" between the two fasteners. The next two fasteners will be 11" down from the top two fasteners, 1/2" inboard of each side of the panel and 2" between the two fasteners. The last two will be 10" down from the second set of fasteners, 1/2" inboard of each side of the panel and 2" between the two fasteners.
5. Install and secure the starboard panel the same as the port panel.

Revision Dates:

Expected Time: 20 min.

Page