

356 SOP SLIDER TOP PLATE INSTALLATION



LOCATION OF SLIDER TOP PLATES



INBOARD EDGES OF TRACK AND TOP PLATE SHOULD BE FLUSH



SLIDE TOP PLATE ALL THE WAY FORWARD UNTIL IT CONTACTS SEAHOOD.

ROUNDED CORNER GOES AFT-INBOARD

#	#Ea.	Description	Size	Part #
1	2	Port and Starboard Top Plate	356	888888
2	8	Top Plate Fastener	#10 x 1" O/H	

1. The slider top plates go over the companion hatch slider tracks. There is a port and starboard piece.
2. Place the top plates in position so the countersinks are facing up and the rounded corner is the aft-inboard corner. The tracks should be slid all the way forward until they make contact with the seahood. The inboard edge of the top plate should be flush with the inboard edge of the top rail of the slider track.
3. Mark the mounting hole locations then remove the top plates and drill the marked locations with a 5/23" drill bit.
4. Dremel the holes to expose raw glass then clean the deck and hardware with alcohol.
5. Caulk the holes with white 739 caulk then secure the top plates to the deck using #10 x 1" oval head screws.
6. Clean up excess caulk with alcohol.

Revision Dates:

Expected Time: 10 min.