

HUNTER 430 STANDING RIGGING SPECIFICATIONS

STANDING RIGGING

FITTINGS

Description	Wire Size	Upper End	Lower End	Overall Length
Upper Upper	3/8 (9 mm)	Stemball w/shell	Aircraft Eye	15' 10" (4.83 m)
Lower Upper	3/8 (9 mm)	Aircraft Eye	12-20-20	36' 3 1/4" (11.06 m)
Upper Intermediate	5/16 (8 mm)	Stemball w/cup	Marine Eye 1/2" pin	17' 2 3/4" (5.25 m)
Lower Intermediate	5/16 (8 mm)	Marine Eye 1/2" pin	10-20-20	19' 9 1/8" (6.02 m)
Lower	3/8 (9 mm)	Stemball w/cup	12-20-20	20' 5 5/8" (6.24 m)
Upper Diamond	1/4 (6 mm)	Marine Eye	8-16-16*	16' 10 1/4" (5.14 m)
Lower Diamond	1/4 (6 mm)	Marine Eye	8-16-16*	19' 0 1/2" (5.80 m)
Forestay	3/8 (9 mm)	Marine Eye	12-20-20	52' 2 3/4" (15.92 m)
Staysail Stay	9/32 (7 mm)	Stemball w/shell	9-16-16	36' 9 5/8" (11.27 m)

All wire is 1 x 19 stainless steel.

* The three numbers represent the turnbuckle size as follows:
Wire size, body size, pin diameter in 32nds (.8 mm) of an inch.